

BASE

APPLICATION GUIDE

EFFLORESCENCE REMOVER 925

APPLICATION INSTRUCTIONS

Description

Efflorescence Remover 925 is a safe and effective solution for removal of white powdery calcium deposits (referred to as efflorescence) which can form on bricks, blocks, concrete, rammed earth and tiles. Efflorescence can occur when calcium deposits are leached out of wet masonry as it dries out and often appearing along mortar or grout lines.

Preparation

Always wear gloves and protective goggles during use. Be careful not to splash onto surrounding surfaces and rinse immediately with water to neutralise if this occurs. Work in smaller sections and avoid unnecessary contact with mortar and bricks on vertical surfaces.

Application

Wipe affected area with damp cloth to remove as much efflorescence as possible. Wet area to be treated but do not allow water to pond. For light stains dilute 1 part Efflorescence Remover 925 with 1 part water and work solution into area with stiff bristle brush or scouring pad. Allow to stand for approx. 5 minutes then wash liberally with water.

DO NOT ALLOW AREA TO DRY

– apply more solution to keep wet or hose down sooner if drying occurs.

For stubborn stains apply Efflorescence Remover 925 neat but test on a small area first when using on coloured concrete to ensure no change in colour occurs.

DISCLAIMER

Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this guide represents our best scientific and practical knowledge. Any advice, information or assistance provided by Base Coatings in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we are unable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use.